

cabinet types



Cabinet type lathes are the same as the bench models except for underneath drive, spindle speeds and necessary alterations in the headstock. Cabinet has three drawers. Built-in chip pan forms the top of the cabinet.

Drive Interlock Feature

Underneath motor drive lathes have an automatic drive interlock which makes it difficult to open the end gear guard or cone pulley cover until the belt tension lever is placed in the non-drive position.

Variable Speed Drive

Attachment to provide variable speed drive is available for 10-K underneath motor drive lathes. It must be ordered with the lathe and installed at the factory. It changes spindle speed ranges of 325 to 1800 r.p.m. in direct drive and 65 to 360 r.p.m. in back gear drive. Catalog No. CL222

	Bed Length Feet	Between Centers Inches	Crated Weight Pounds	With 16-Speed V-Belt Horizontal Motor Drive Catalog No.	With 12-Speed Flat Belt Drive Catalog No.
Bench	3½	22	505	CL770Z	CL670Z (HMD)
	4½	34	535	CL770R	CL670R (HMD)
Cabinet	3½	22	720		CL370ZD (UMD)
	4½	34	760		CL370RD (UMD)

MOTORS AND CONTROLS

HMD

Cat. No.	H. P.	Speed	Phase	Cycle	Voltage	Drum Control	P. B. Linestarter
CE4920B	½	1	1	60	115	EHB790	EB841AO
CE4920D	½	1	1	60	230	EHB790	EB841CO
CE4924P	½	1	3	60	208	EHB790	EB841CO
CE4924D	½	1	3	60	230	EHB790	EB841CO
CE4924F	½	1	3	60	460	EHB790	EB841DTO


Note: Push button controls are supplied unmounted for horizontal motor drive lathes.

UMD

CE4920B	½	1	1	60	115	EB790	EB841AO
CE4920D	½	1	1	60	230	EB790	EB841CO
CE4924P	½	1	3	60	208	EB790	EB841CO
CE4924D	½	1	3	60	230	EB790	EB841CO
CE4924F	½	1	3	60	460	EB790	EB841DTO

VARIABLE SPEED

CE2804	¾	1	1	60	115	EB790	EB841AO
CE2805	¾	1	1	60	230	EB790	EB841CO
CE2801D	¾	1	3	60	230	EB790	EB841CO
CE2801F	¾	1	3	60	460	EB790	EB841DTO



10-K HORIZONTAL MOTOR DRIVE GAP BED LATHES

Bed Length 4½'
 Between Centers 34"
 Crated Weight, pounds 565
 Catalog Number **CL770RG** with 16-speed V-belt drive.
 Catalog Number **CL670RG** with 12-speed flat belt drive.

